

**ADSORPTIVE TREATMENT OF TEXTILE WASTEWATER
USING ACTIVATED CARBON PREPARED FROM PANDANUS
AMARYLLIFOLIUS STEMS AND ARECA CATECHU FRONDS**

by

MUHD NAZMI ISMAIL

**Thesis submitted in fulfillment of the
requirements for the degree of
Doctor of Philosophy**

February 2016

ACKNOWLEDGEMENT

In The Name of Allah, The Beneficent, The Merciful.

My foremost, thanks go to Allah Almighty for He has blessed me with spiritual strength guidance. I am very much indebted to my coordinating supervisor, Prof. Dr. Hj. Hamidi Abdul Aziz for his dedication and commitment. My heartfelt thanks to my co-supervisor, Assoc. Prof. Dr. Hj. Mohd Azmier Ahmad for his advice and assistance. Not to dismiss from the list of helpful individuals are my family, especially my beloved wife Syahira Mohd Zayadi, my children Nur Dini Alya Muhd Nazmi, Ahmad Danial Adam Muhd Nazmi and Arfa Damia Muhd Nazmi as well as my parents and my parent-in-law for their constant support and motivation. Special acknowledgement goes to research colleague; Mohamad Anuar Kamaruddin, Khairul Azuan Abdullah, Mohd Faiz Muaz, Muhammad Azan Tamar Jaya, Nur Hidayah Ahmad and Mohd Faisal Ahmad for sharing their knowledge, professional advices and guidelines throughout the whole project.

For the financial support, I would like to thank Universiti Sains Malaysia for the Research University Grant (RU-PRGS: 1001/PAWAM/8046009), Solid Waste Management Grant (1001/CKT/870023) and *Hadiah Latihan Persekutuan* (HLP) Scheme funded by Ministry of Higher Education, Malaysia. Lastly, I would like to extend my gratitude to those who were indirectly involved in my research. Thank you for all.

Muhd Nazmi Bin Ismail

February 2016

TABLE OF CONTENTS

Acknowledgement	ii
Table of Contents	iii
List of Tables	ix
List of Figures	xv
List of Plates	xx
List of Abbreviations	xxi
List of Symbols	xxiii
Abstrak	xxv
Abstract	xxvii

CHAPTER 1 - INTRODUCTION

1.0	Background	1
1.1	Pollutants Removal	2
1.1.1	Dyes	2
1.1.2	Colorant	3
1.1.3	Chemical Oxygen Demand	4
1.2	Biomass- based Activated Carbon	5
1.3	Problem Statement	6
1.4	Scope of Study	9
1.5	Research Objectives	10
1.6	Organization of Thesis	10

CHAPTER 2 - LITERATURE REVIEW

2.1	Textile Industry	12
2.2	Textile Processes	13
2.3	Textile Wastewater Characteristics and Environmental Impact	14
2.4	Textile Wastewater Treatment	17
2.4.1	Biological Treatment	18
2.4.2	Physico-chemical Treatment	20
2.4.2(a)	Coagulation and Flocculation	21
2.4.2(b)	Chemical Oxidation	22
2.4.2(c)	Membrane Filtration	25
2.4.2(d)	Ion Exchange	28
2.4.2(e)	Adsorption	30
2.4.2(f)	Present Condition of Activated Carbon	34
	Adsorption	
2.4.3	Combined Physico-chemical and Biological Methods	36
2.4.4	Summary of Textile Wastewater Strategies	37
2.5	Activated Carbon	40
2.6	Activated Carbon Precursor	43
2.6.1	Pandanus Amaryllifolius (P. Amaryllifolius)	46
2.6.2	Areca Catechu (A. Catechu)	47
2.7	Preparation Method of Activated Carbon from Biomass	49
2.8	Influence of Preparation Variable to Activated Carbon	53
2.9	Optimization of Preparation Conditions of Activated Carbon	58
2.10	Characterization of Activated Carbon	59
2.10.1	Activated Carbon Yield	59

2.10.2	Surface Area and Pore Characteristics	59
2.10.3	Surface Morphology of Activated Carbon	60
2.10.4	Proximate Analysis	61
2.10.5	Surface Chemistry	63
2.11	Adsorption Isotherm	63
2.11.1	Langmuir Isotherm	64
2.11.2	Freundlich Isotherm	65
2.12	Adsorption Kinetics	66
2.12.1	Pseudo-first-order Kinetic Model	66
2.12.2	Pseudo-second-order Kinetic Model	67
2.12.3	Elovich Kinetic Model	67
2.12.4	Avrami Kinetic Model	67
2.13	Fixed-bed Flow System Behavior	68
2.13.1	Process Behaviour	68
2.13.2	Analysis of Column Data	69
2.14	Breakthrough Curve Modeling	71
2.15	Activated Carbon Regeneration	73
2.16	Gap of Study	76

CHAPTER 3 - MATERIALS AND METHODS

3.1	Materials	78
3.2	Textile Industry Wastewater	81
3.2.1	Sampling Procedure	81
3.2.2	Site Location and Wastewater Characteristics	81
3.3	Analytical Methods	84

3.4	General Description of Equipment	85
3.4.1	Activated Carbon Preparation	85
3.4.2	Batch Adsorption and Analysis System	86
3.4.3	Characterization System	87
3.5	Experimental Procedure	89
3.5.1	Precursor Preparation	89
3.5.2	Activated Carbon Synthesization	90
3.5.2(a)	Carbonization	90
3.5.2(b)	KOH Impregnation	90
3.5.2(c)	Carbon Dioxide Gasification	91
3.5.3	Experimental Design	91
3.5.4	Batch Equilibrium Studies	94
3.5.4(a)	Effect of Initial Adsorbate Concentration and Contact Time	94
3.5.4(b)	Determination of the Adsorption Isotherm	95
3.5.5	Batch Kinetic Studies	95
3.6	Fixed-bed Study	96
3.6.1	Effect of Flowrates	98
3.6.2	Effect of Initial Concentration and Bed Height	99
3.7	Regeneration of Spent Activated Carbon	99
3.8	Experimental Flow Chart	101

CHAPTER 4 - RESULTS AND DISCUSSIONS

4.1	Experimental Design	102
4.1.1	Preparation of PSAC Using Design of Experiment	102

4.1.1 (a)	Development of Regression Model Equation For Preparation of PSAC	102
4.1.1(b)	Effect of Variables onto Responses for PSAC	110
4.1.2	Preparation of PFAC using Design of Experiment	116
4.1.2(a)	Development of Regression Model Equation For Preparation of PFAC	116
4.1.2 (b)	Effect of Variables onto Responses for PFAC	122
4.1.3	Optimization of Operating Parameters	128
4.2	Characterization of Activated Carbon	131
4.2.1	Surface Area and Pore Characteristics	131
4.2.2	Surface Morphology	133
4.2.3	Proximate Analysis	136
4.2.4	Surface Chemistry	136
4.3	Batch Adsorption Studies onto PSAC and PFAC	138
4.3.1	Batch Equilibrium Studies	139
4.3.1 (a)	Adsorption Equilibrium for Synthetic Wastewater (Dyes)	139
4.3.1 (b)	Adsorption Equilibrium for Actual Textile Wastewater	142
4.3.2	Adsorption Isotherm for Synthetic Wastewater	143
4.3.3	Adsorption Isotherm for Actual Textile Wastewater	149
4.3.4	Batch Kinetic Studies	150
4.4	Fixed-bed Adsorption Studies	162

4.4.1	Effect of Solution Flowrate	163
4.4.2	Effect of Activated Carbon Bed Height	164
4.4.3	Effect of Inlet Concentration	172
4.5	Dynamic Adsorption Models	173
4.5.1	Adam-Bohart Model	173
4.5.2	Thomas Model	177
4.5.3	The Yoon-Nelson Model	180
4.6	Spent Activated Carbon Regeneration	182
4.7	Summary of Findings	184

CHAPTER 5 - CONCLUSIONS AND RECOMMENDATIONS

5.1	Conclusions	190
5.2	Recommendations	191

REFERENCES	192
------------	-----

APPENDICES

Appendix A	Plots of adsorption versus time
Appendix B	Figures of dynamic adsorption models (Adam-Bohart, Thomas and Yoon-Nelson)

LIST OF PUBLICATIONS

LIST OF TABLES

	Page
Table 2.1	Characteristics of cotton textile industry wastewater 16
Table 2.2	Sources of pollution in textile manufacturing 16
Table 2.3	Aerobic and anaerobic of textile wastewater treatment 20
Table 2.4	Treatment of dye containing wastewater and their removal efficiencies by coagulation and flocculation 22
Table 2.5	Classification of conventional AOPs 23
Table 2.6	Comparison of physical and chemical adsorption 34
Table 2.7	Combined physicochemicals and biological methods 38
Table 2.8	Adsorption of various dyes using commercial ACs 43
Table 2.9	Adsorption capacities for ACs derived from biomass wastes 44
Table 2.10	Commercial ACs used in synthetic dyes wastewater treatment 45
Table 2.11	Agricultural wastes used to prepare lowcost ACs 46
Table 2.12	Precursor used for AC production in synthetic dyes removal 46
Table 2.13	Carbonization process 49

Table 2.14	Common activation methods for preparation of AC	51
Table 2.15	Previous work carried out on physical activation	52
Table 2.16	Previous work carried out on chemical activation	52
Table 2.17	Previous work carried out on physicochemical activation	53
Table 2.18	Effects of preparation conditions for activated carbon production	56
Table 2.19	Physical characteristics of AC produced from various precursors	60
Table 2.20	Proximate analysis of AC	62
Table 2.21	FTIR spectrum band assignments for pistachio-nut shell AC	63
Table 2.22	Previous work on activated carbon desorption	75
Table 2.23	Comparison of activated carbon regeneration efficiency	75
Table 3.1	List of chemicals	79
Table 3.2	Properties of methylene blue	79
Table 3.3	Properties of methyl red	80
Table 3.4	Properties of remazol brilliant violet 5R	80
Table 3.5	Characteristics of textile wastewater	82

Table 3.6	Independent variable and their coded levels for the CCD	92
Table 3.7	Experimental design matrixes	93
Table 3.8	Operational parameters of the experimental set up for the column study	97
Table 4.1	Matrix for PSAC preparation variables and responses	104
Table 4.2	ANOVA analysis for MB removal for PSAC	106
Table 4.3	ANOVA analysis for MR removal for PSAC	106
Table 4.4	ANOVA analysis for RBV removal for PSAC	107
Table 4.5	ANOVA analysis for PSAC yield	107
Table 4.6	ANOVA analysis for color removal for PSAC	108
Table 4.7	ANOVA analysis for COD removal for PSAC	108
Table 4.8	Matrix for PFAC preparation variables and responses	117
Table 4.9	ANOVA analysis for MB removal for PFAC	120
Table 4.10	ANOVA analysis for MR removal for PFAC	120
Table 4.11	ANOVA analysis o for RBV removal for PFAC	121
Table 4.12	ANOVA analysis for PFAC yield	121
Table 4.13	ANOVA analysis for color removal for PFAC	122

Table 4.14	ANOVA analysis for COD removal for PFAC	122
Table 4.15	Model validation for activated carbon prepared for MB, MR, RBV color and COD	130
Table 4.16	Surface area and pore characteristics of the prepared activated carbons	131
Table 4.17	Proximate analysis for the prepared activated carbons	136
Table 4.18	FTIR spectrum band assignments for PS, PS Char and PSAC	137
Table 4.19	FTIR spectrum band assignments for PF, PF Char and PFAC	138
Table 4.20	Isotherm parameters for PSAC and PFAC (synthetic wastewater) at temperature 30°C	148
Table 4.21	Isotherm parameters for PSAC and PFAC (color) at temperature 30°C	150
Table 4.22	Isotherm parameters for PSAC and PFAC (COD) at temperature 30°C	150
Table 4.23	Kinetic model parameter for PSAC (MB) adsorption at 30°C	155
Table 4.24	Kinetic model parameter for PFAC (MB) adsorption at 30°C	156
Table 4.25	Kinetic model parameter for PSAC (MR) adsorption at 30°	157

Table 4.26	Kinetic model parameter for PFAC (MR) adsorption at 30°C	158
Table 4.27	Kinetic model parameter for PSAC (RBV) adsorption at 30°C	159
Table 4.28	Kinetic model parameter for PFAC (RBV) adsorption at 30°C	160
Table 4.29	Performance of absorbates on PSAC at 100 mg/L initial concentration for synthetic wastewater and fixed values for real wastewater, 10 mL/min flow rate and 120 mm bed height	163
Table 4.30	Performance of absorbates on PFAC at 100 mg/L initial concentration for synthetic wastewater and fixed values for real textile wastewater, 10 mL/min flow rate and 120 mm bed height	163
Table 4.31	Adam-Bohart model parameters for fixed bed adsorption of pollutants on PSAC at different flowrates	176
Table 4.32	Adams-Bohart model parameters for fixed bed adsorption of pollutant on PFAC at different flowrates	177
Table 4.33	Thomas model parameters for fixed bed adsorption of pollutant removal onto PSAC at different flowrates	178
Table 4.34	Thomas model parameters for fixed bed adsorption of pollutant removal onto PFAC at different flowrates	179

Table 4.35	Yoon-Nelson model parameters for fixed bed adsorption of pollutants removal onto PSAC at different flowrates	180
Table 4.36	Yoon- Nelson model parameters for fixed bed adsorption of pollutant removal onto PFAC at different flowrates	181
Table 4.37	Comparison of R^2 values between Adam-Bohart, Thomas and Yoon-Nelson models (PSAC/ PFAC)	182
Table 4.38	Ethanol regeneration efficiency (%) for MB, MR, RBV color and COD adsorption-desorption onto PSAC and PFAC	184

LIST OF FIGURES

	Page
Figure 2.1 Electrochemical oxidation configuration	25
Figure 2.2 Mechanism of adsorption and desorption	32
Figure 2.3 Breakthrough curve in up-flow mode	69
Figure 3.1 Cotton mill process and wastewater treatment sequence	83
Figure 3.2 Wastewater treatment plant system	84
Figure 3.3 Schematic diagram of the experimental setup for activated carbon production	85
Figure 3.4 Batch analysis system	87
Figure 3.5 Schematic diagram of fixed-bed study	98
Figure 3.6 Flow diagram of experimental activities	101
Figure 4.1 Predicted versus experimental for (a) PSAC yield, (b) MB removal, (c) MR removal, (d) RBV removal, (e) color removal and (f) COD removal	109
Figure 4.2 Response surface plot of MB removal (Effect of activation temperature and activation time, IR = 1.75) of PSAC	111
Figure 4.3 Response surface plot of MR removal (Effect of activation temperature and IR, activation time = 2 h) of PSAC	112

Figure 4.4	Response surface plot of RBV removal (Effect of activation temperature and IR, activation time = 2 h) of PSAC	113
Figure 4.5	Response surface plot of PSAC yield (Effect of activation temperature and activation time, IR = 1.75)	114
Figure 4.6	Response surface plot of color removal (Effect of activation temperature and IR, activation time = 2 h) of PSAC	115
Figure 4.7	Response surface plot of COD removal (Effect of activation temperature and IR, activation time = 2 h) of PSAC	116
Figure 4.8	Predicted versus experimental for (a) MB removal, (b) MR removal, (c) RBV removal, (d) PFAC yield (e) color and (f) COD	119
Figure 4.9	Response surface plot of MB removal (Effect of activation time and activation temperature, IR = 1.75) of PFAC	123
Figure 4.10	Response surface plot of MR removal (Effect of activation temperature and IR, activation time = 2 h) of PFAC	124
Figure 4.11	Response surface plot of RBV removal (Effect of activation temperature and IR, activation time= 2 h) of PFAC	125
Figure 4.12	Response surface plot of PFAC yield (Effect of activation temperature and activation time, IR = 1.75)	126

Figure 4.13	Response surface plot of color removal (Effect of activation temperature and activation time, IR = 1.75 of PFAC	127
Figure 4.14	Response surface plot of COD removal (Effect of activation temperature and IR, activation time = 2 h) of PFAC	128
Figure 4.15	MB percent removals versus adsorption time at various initial concentrations at 30 °C (a) PSAC and (b) PFAC	140
Figure 4.16	MR percent removals versus adsorption time at various initial concentrations at 30 °C (a) PSAC and (b) PFAC	142
Figure 4.17	MB percent removals versus adsorption time at various initial concentrations at 30 °C (a) PSAC and (b) PFAC	142
Figure 4.18	Color percent removals versus adsorption time at 30 °C; (a) PSAC and (b) PFAC	143
Figure 4.19	COD percent removal versus adsorption time at 30 °C (a) PSAC and (b) PFAC	143
Figure 4.20	Plots of (a) Langmuir and (b) Freundlich isotherms for MB adsorption on PSAC at 30 °C	145
Figure 4.21	Plots of (a) Langmuir and (b) Freundlich isotherms for MB adsorption on PFAC at 30 °C	145
Figure 4.22	Plots of (a) Langmuir and (b) Freundlich isotherms for MR adsorption on PSAC at 30 °C	146

Figure 4.23	Plots of (a) Langmuir and (b) Freundlich isotherms for MR adsorption on PFAC at 30 °C	146
Figure 4.24	Plots of (a) Langmuir and (b) Freundlich isotherms for RBV adsorption on PSAC at 30°C	147
Figure 4.25	Plots of (a) Langmuir, (b) Freundlich, isotherms for RBV adsorption on PFAC at 30°C	147
Figure 4.26	Plots of separation factor versus MB initial concentration for adsorption of PSAC and PFAC at 30°C	148
Figure 4.27	Plots of separation factor versus MR initial concentration for adsorption of PSAC and PFAC at 30°C	149
Figure 4.28	Plots of separation factor versus MR initial concentration for adsorption of PSAC and PFAC at 30°C	149
Figure 4.29	Linerized plots of (a) pseudo-first-order, (b) pseudo-second-order, (c) Avrami and (d) Elovich kinetic model for MB adsorption on PSAC at 30°	151
Figure 4.30	Linerized plots of (a) pseudo-first-order, (b) pseudo-second-order, (c) Avrami and (d) Elovich kinetic model for MB adsorption on PFAC at 30°C	152
Figure 4.31	Linerized plots of (a) pseudo-first-order, (b) pseudo-second-order, (c) Avrami and (d) Elovich kinetic model for MR adsorption on PSAC at 30°C	153
Figure 4.32	Linerized plots of (a) pseudo-first-order, (b) pseudo-second-order, (c) Avrami and (d) Elovich kinetic model for RBV adsorption on PSAC at 30°C	154

Figure 4.33	Breakthrough curves for a) MB, b) MR and c) RBV adsorption onto PSAC at different flowrate.	165
Figure 4.34	Breakthrough curves for a) MB b) MR and c) RBV adsorption onto PFAC at different flowrate.	166
Figure 4.35	Breakthrough curves for a) colour and b) COD adsorption onto PSAC at different flowrate	167
Figure 4.36	Breakthrough curves for a) color and b) COD adsorption onto PFAC at different flowrate	168
Figure 4.37	Breakthrough curves for MB, MR and RBV adsorption onto PFAC at different bed height	169
Figure 4.38	Breakthrough curves for MB, MR and RBV adsorption onto PFAC at different bed height	170
Figure 4.39	Breakthrough curves for color and COD adsorption onto PFAC at different bed height	171
Figure 4.40	Breakthrough curves for color and COD adsorption onto PFAC at different bed height	172
Figure 4.41	Breakthrough curves for MB, MR and RBV adsorption onto PSAC at different initial concentration.	174
Figure 4.42	Breakthrough curves for MB, MR and RBV adsorption onto PFAC at different initial concentration	175

LIST OF PLATES

		Page
Plate 2.1	Pandanus amaryllifolius plant	47
Plate 2.2	Areca catechu plant	48
Plate 2.3	Scanning electron micrographs (a) MP, (b) MP char and (c) MP activated carbon (magnifications: 500x) (Ahmad and Alrozi, 2010)	61
Plate 3.1	Sampling pipe (Buffer pit)	81
Plate 3.2	Precursors a) Pandanus amaryllifolius stems and b) Areca catechu fronds	89
Plate 4.1	Scanning electron micrographs (a) PS char and (b) PSAC (magnifications: 15000x)	134
Plate 4.2	Scanning electron micrographs (a) PF char and (b) PFAC (magnifications: 15000x)	135

LIST OF ABBREVIATIONS

AC	Activated carbon
AOP	Advanced Oxidation Process
ANOVA	Analysis of Variance
APHA	American Public Health Association
BOD	Biochemical Oxygen Demand
BET	Brunauer-Emmett-Teller
CCD	Central Composite Design
COD	Chemical Oxygen Demand
FTIR	Fourier Transform Infrared
GAC	Granular Activated Carbon
HRT	Hydraulic Retention Time
IR	Impregnation Ratio
IUPAC	International Union of Pure and Applied Chemistry
MB	Methylene Blue
MR	Methyl Red
MSDS	Material Safety Data Sheet
MTZ	Mass Transfer Zone
N	Total Number of Sample
NCB	Nano Carbon Bead
NF	Nanofiltration
OFAT	One Factor at Time
PAC	Powder Activated Carbon
PACl	Polyaluminium Chloride
PBBR	Pebble Bed Photocatalytic Reactor
PSAC	Pandanus Amaryllifolius Stems Activated Carbon
PFAC	Pinang Fronds Activated Carbon
RBV	Remazol Brilliant Violet 5R
RO	Reverse Osmosis
RO/NF	Reverse Osmosis/Nanofiltration
RSM	Response Surface Methodology

SEM	Scanning Electron Microscopy
STA	Simultaneous Thermogravimetric Analyser
UF	Ultrafiltration
UV	Ultraviolet

LIST OF SYMBOLS

		Unit
A	Arrhenius factor	-
A_i	Measured absorbance for component i	-
C	Solute/outlet concentration	mg/L
C_e	Concentration of adsorbate at equilibrium	mg/L
C_i	Constant for Intraparticle diffusion model	mg/g
C_t	Concentration of adsorbate at time, t	mg/L
C_o	Initial/inlet adsorbate concentration	mg/L
D_p	Average pore diameter	nm
E_a	Arrhenius activation energy of adsorption	kJ/mol
F	Fraction of solute adsorbed for Boyd model	-
K_F	Adsorption or distribution coefficient for Freundlich isotherm	mg/g (L/mg) ^{1/n}
K_L	Rate of adsorption for Langmuir isotherm	L/mg
k_{Av}	Avrami kinetic constant	-
k_{pi}	Adsorption rate constant for intraparticle diffusion model	mg/g h ^{1/2}
k_1	Adsorption rate constant for pseudo-first-order	1/h
k_2	Adsorption rate constant for pseudo-second-order	g/mg h
N	Total number of experiments required/data point	-
n_{Av}	Avrami kinetic constant	-
n_F	Constant for Freundlich isotherm	-
n_{KC}	Adsorption intensity Koble-Corrigan isotherm	-
n_{To}	Toth constant	mg/g
Q_o	Adsorption capacity for Langmuir isotherm	mg/g
Q_m	Maximum adsorption capacity of adsorbent	mg/g
q_e	Amount of adsorbate adsorbed per unit mass of adsorbent at equilibrium	mg/g
q_t	Amount of adsorbate adsorbed per unit mass of adsorbent at time, t	mg/g
$q_{t, cal}$	Calculated adsorption uptake at time, t	mg/g

$q_{t, exp}$	Experimental adsorption uptake at time, t	mg/g
R	Universal gas constant	8.314 J/mol K
R_L	Separation factor	-
R^2	Correlation coefficient	-
S_{BET}	BET surface area	m ² /g
T	Absolute temperature	K
T	Time	h
V	Volume of the solution	L
V_{meso}	Mesopore volume	cm ³ /g
V_T	Total pore volume	cm ³ /g
W	Mass of adsorbent	g
w_c	Dry weight of prepared activated carbon	g
w_o	Dry weight of precursor	g
	Dry weight of sodium carbonate	g
X	Activated carbon preparation variable	-
Y	Predicted response	-

Greek letters

ΔG^o	Changes in standard free energy	kJ/mol
ΔH^o	Changes in standard enthalpy	kJ/mol
Δq_t	Normalized standard deviation	%
ΔS^o	Changes in standard entropy	J/mol K
α_{El}	initial desorption rate for Elovich kinetic model	mg/(g min)
α_t	adsorption fraction of time of Avrami kinetic model	-
λ or λ	Wavelength	nm
β_{El}	desorption constant for Elovich kinetic model	g/mg